



QINGDAO TONGJIA TEXTILE MACHINERY CO., LTD



Mini Rotor Spinning Machine
Model: 1603

Feature:

This miniature type machine is used to Separation of fibers by rigorous drafting and the then recollection and twisting of fibers in a rotor for impart sufficient twist to the fibres to from continuous yarn and wind up the spun yarn into package form.

Model	1603
Condition	Brand new and latest version
Control system	PLC control automatic system
Display type	Digital LCD Display
Display size	7"
Unit	24 units
Gauge	200
Max rotor speed	75000 rpm or standard
Rotor Dia.	34-66mm
Rotational speed of opening/combing roller	5000 – 11000 rpm
Opening/combing roller diameter	Ø 56- 65 mm
Density of optimal yarn	120 – 15 tex
Draft ratio	20-280
Feed sliver count	0.2-0.45 mm
Twist rage	200 – 2000 twist/meter
Air capacity of air exhaust fan	1800Pa
Can size	300×900 or 400×1100mm
Suction system	Automatic/ continuous suctioning system.
Power supply	380-440V, 50Hz, 3 phase
Energy consumption	11kw
Weight	4100kg
Dimension	4100x1100x1830mm
Max. height	13.5 feet



QINGDAO TONGJIA TEXTILE MACHINERY CO., LTD

Address: Wangtai Town, Jiaonan Qingdao, P.R. China.



Phone :

Tel: +0086-532-86228100

Fax: +0086-532-86228100



Email :

davidding@chinatongjia.cn



Website :

<http://www.chinatongjia.com>